

Bobcat Large Air Compressors

1350–1400 CFM



Key Specifications

	PA1350P (Bunded Base)	PA1350P	PA1400P	PA1350P (Volvo)
Free Air Delivery	1350 (38.23) cfm (m ³ /min)	1350 (38.2) cfm (m ³ /min)	1400 (39.62) cfm (m ³ /min)	1350 (38.2) cfm (m ³ /min)
Pressure	350/365 (24.2/25.2) psi (bar)	365/400 (25.2/27.6) psi (bar)	350/385 (24.1/26.5) psi (bar)	335/350/375 (23.1/24.1.2/25.8) psi (bar)
Engine	Volvo - TAD1345VE	Cummins - KTA1150	Cummins - KTA1150	Volvo - TAD1345

Compressor - Rotary Screw

	PA1350P (Bunded Base)	PA1350P	PA1400P	PA1350P (Volvo)
Number of Stages	2	2	2	2
Free-Air Delivery	1350 (38.2) cfm (m ³ /min)	1350 (38.2) cfm (m ³ /min)	1400 (39.62) cfm (m ³ /min)	1310 (37) cfm (m ³ /min)
Operating Pressure	350/365 (24.2/25.2) psi (bar)	365/400 (25.2/27.6) psi (bar)	350/385 (24.1/26.5) psi (bar)	335/350/375 (23.1 /24.1/25.8) psi (bar)
Pressure Range	150 - 385 (10.5 - 26.5) psi (bar)	150 - 420 (10.5 - 29) psi (bar)	150 - 420 (10.5 - 29) psi (bar)	150 - 375 (10.5 - 25.8) psi (bar)
Air Discharge Outlet Size	2 (50.8) in (mm)	2 (50.8) in (mm)	2 (50.8) in (mm)	2 (50.8) in (mm)
Air Discharge Outlet Quantity	1	1	1	1

▲ PA1350P Features ¹

▲ Features

- Faster drilling in its class.
- Fuel efficient in its class.
- ATC system for fuel efficient.
- Reliable Package.
- Dual pressure mode 350/365 psi.
- Compact version, maximises utility on truck.
- Silent version and eco friendly.
- 3-layer coating with lifetime coverage.
- Zero maintenance batteries, with more cranks per start.
- Starter protection unit.
- Wide doors to ease serviceability.
- 3 stage air filtrations with pre cleaners.
- Designed to operate between 5° C to 52° C.
- Best in ownership cost.

▲ PA1350P (Volvo) Features ¹

▲ Features

- Faster drilling in its class.
- Fuel efficient in its class.
- ATC system for fuel efficient.
- Reliable Package.
- Convertible pressure 335-350/375
- Compact version, maximises utility on truck.
- Silent version and eco-friendly.
- 3-layer coating with lifetime coverage.
- Zero maintenance batteries, with more cranks per start.
- Starter protection unit.
- Wide doors to ease serviceability.
- 3 stage air filtrations with pre cleaners.
- Designed to operate between 5° C to 52° C.
- Best in ownership cost.

▲ PA1400P Features 1

▲ Features

- Faster drilling in its class.
- Fuel efficient in its class.
- ATC system for fuel efficient.
- Split Package.
- Dual pressure mode 350/385 psi.
- Compact version, maximises utility on truck.
- Silent version and eco-friendly.
- 3-layer coating with lifetime coverage.
- Zero maintenance batteries, with more cranks per start.
- Starter protection unit.
- Wide doors to ease serviceability.
- 3 stage air filtrations with pre cleaners.
- Designed to operate between 5° C to 52° C.
- Best in ownership cost.

▲ PA1350P Bunded Base Features 1

▲ Features

- Faster drilling in its class.
- Fuel efficient in its class.
- ATC system for fuel efficient.
- Reliable Package.
- Dual pressure mode 350/365 psi.
- Compact version, maximises utility on truck.
- Silent version and eco friendly.
- 3-layer coating with lifetime coverage.
- Zero maintenance batteries, with more cranks per start.
- Starter protection unit.
- Wide doors to ease serviceability.
- 3 stage air filtrations with pre cleaners.
- Designed to operate between 5° C to 52° C.
- Best in ownership cost.

Engine				
	PA1350P (Bunded Base)	PA1350P	PA1400P	PA1350P (Volvo)
Make	Volvo	Cummins	Cummins	Volvo
Model	TAD1345	KTA1150	KTA1150	TAD1345
Emission Norms	Tier 2	Non-Emission	Non-Emission	Non-Emission
Number of Cylinders	6	6	6	6
Power Rating	536 (400) hp (kW)	585 (436) hp (kW)	585 (436) hp (kW)	536 (400) hp (kW)
Full Speed	1900 rpm	1950 rpm	1950 rpm	1900 rpm
Cooling System Drive	Hydraulic System	Hydraulic System	Hydraulic System	Hydraulic System
Idle Speed	1200 rpm	1200 rpm	1200 rpm	1250 rpm

Electrical System				
	PA1350P (Bunded Base)	PA1350P	PA1400P	PA1350P (Volvo)
Battery Rating	24V 160Ah	24V 160Ah	24V 160Ah	24V 160Ah

Dimensions Without Running Gear				
	PA1350P (Bunded Base)	PA1350P	PA1400P	PA1350P (Volvo)
Length	3880 (153) mm (in)	6090 (240) mm (in)	6090 (240) mm (in)	3900 (153.5) mm (in)
Width	1700 (66.9) mm (in)	2222 (87.5) mm (in)	2222 (87.5) mm (in)	2000 (78.7) mm (in)
Height	1950 (76.7) mm (in)	3067 (120.8) mm (in)	3067 (120.8) mm (in)	1975 (77.7) mm (in)
Gross Weight	4900 (108.3) kg (lbs)	6250 (137.7) kg (lbs)	6250 (137.7) kg (lbs)	5190 (11442) kg (lbs)